

TEXA

RUGGED CONNECTIVITY

ADVANCED DIAGNOSTICS & PROTOCOLS SPECIFICALLY DEVELOPED TO SUPPORT ACCESS FOR POWERSPORTS AND MARINE ENVIRONMENTS

TEXA TXB2

Support repair technicians with essential diagnostic operations, including error reading and clearing, display of engineering parameters and status of control unit, activations, adjustments and configurations of the vehicle devices, deactivation of the warning lights, configuration of the control units, fuel trim and injection timing.



LED DISPLAY

Optimize Data Download Useability With New RGB LED Confirmation



Blink Codes / K, L, FD CAN 11898-2 CAN ISO 11898-3

DYNAMIC TEST

Rugged Design For Safe Parameter Recording Session While Moving



CAN SAE J2411 SAE J1850 SAE J1708 / RS232

POWERFUL

Faster Processor With Latest Protocols For Precise Recording Of Data From Control Units



Cortex M7 550 MHz Processor 1MB Flash / 256 MBit SRAM 8 GByte eMMC Memory

COVERAGE

Integrated 16-Pin Connector Latest Generation Bluetooth New USB C Data Download



16 Pin CPC Connector Wireless Bluetooth 5.0 High Speed 2.0 USB C

292 FERNWOOD AVE EDISON, NJ 08837

NORTHAMERICA@TEXA.COM

WWW.TEXAUSA.COM



MADE IN ITALY / OEM PARTNER